

Flame retardant Tape SV-9140J-B


Ver.04

FEB.2022

General Description SV-9140J-B is an environmentally friendly (toluene free), flame resistant (UL94 VTM-0) tape without halogen and antimony.

FILE No.: E524257

Product Construction



Thickness: 0.140mm Liner type: Paper

Characteristics

- Raw materials don't contain the 13 kinds of hazardous materials that Health Ministry of Japan's designated
- TO free, the total VOC content is lower than ordinary products, and is more suitable for indoor or closed space use.
- Use halogen free flame retardant for material, Compliance with ROHS 2.0 and halogen requirements
- Flame retardant grade amount to UL94 VTM-0 level
- Excellent performance under a wide range of temperature.

Applications

- Bonding electric parts such as home appliances, OA equipment
- Bonding Automobile Interior Materials for doors, roofs, air-condition etc.
- For application of flame-retardant materials

Properties

Item	Value	Test Procedures
Peel Strength (N/20mm)	13.2	180 degree peel at 300mm/min 23°C 50%RH, to SUS plate, 20min dwell
Holding Power (mm)	0.3	weight held for 1 hour to SUS with 20×20mm overlap, 1Kg at 40°C, 20min dwell
Ball Tack	15	23°C50%RH, according to J.Dow method
Flame Retardant	VTM-0	UL94 standard

Shelf Life

12 months from date of manufacture when stored in original cartons at -5~40°C and relative humidity below 70%

IMPORTANT NOTICE: The above figures are taken from experiments conducted under standard conditions at Soken. They are not for guaranteed, just for your reference only.

TEL: 0574-86768175

FAX: 0574-86768176

URL: <http://www.ningbo-soken.com>

E-mail: marketing@ningbo-soken.com