

PE laminated cloth tape CW-17C


Ver.03

Technical Data Sheet

Nov.2021

General Description Soken tape CW-17C is PE laminated cloth tape based on pressure sensitive acrylic adhesive, Which can be used for packing and bonding the products.

Product Construction



Thickness: 0.150 mm

Characteristics

- MD can resist stretching, TD can be torn easily
- Good resistance against weather, water and temperature
- Good adhesion strength and cohesion, high Ball Tack

Applications

- Packing industry.
- Temporary bonding for parts of electrical appliances, automobile and OA machines etc .

Properties

Item	Value	Test Procedures
Peel Strength (N/25mm)	8.4	180 degree peel at 300mm/min 23°C 50%RH, to SUS plate, 20min dwell
Holding Power (mm)	0.5	weight held for 1 hour to SUS with 20mm × 20mm overlap, 1Kg at 40°C, 20min dwell
Ball Tack	24	23°C 50%RH, according to J Dow method

Shelf Life

12 months from date of manufacture when stored in original cartons at -5~40°C and relative humidity below 70%

IMPORTANT NOTICE: The above figures are taken from experiments conducted under standard conditions at Soken. They are not for guaranteed, just for your reference only.

TEL: 0574-86764501

FAX: 0574-86768176

URL: <http://www.ningbo-soken.com>

E-mail: marketing@ningbo-soken.com